

# PRODUCT & TECHNICAL DATA

## TECTION GLOBAL 15W-40 Multigrade engine lubricant

### DESCRIPTION

Castrol Tection Global is a mineral based multigrade engine oil for use in turbocharged and naturally aspirated diesel engines of European, US and Japanese technology.

The versatile formulation used in Tection Global provides protection against wear and deposits, ensuring reduced maintenance costs and preventing unscheduled downtime.

### APPLICATIONS

The viscosity of Tection Global promotes easy starting and efficient lubrication at low temperatures and provides optimum protection at high temperatures without increasing oil consumption. Extensive engine tests have demonstrated that Tection Global produces minimum deposit formation and wear, thereby maintaining engine efficiency.

Tection Global complies with the requirements of engine manufacturers specifying:

API CI-4/CF	ACEA E3/E5/E7
MB 228.3	Volvo VDS-3
MAN M3275	Mack EO-M Plus
Cummins 20,071/2/6/7/8	DHD-1
RVI RLD, RLD-2	

### TECHNICAL DATA

Typical Characteristics	Tection Global 15W-40
Density @ 15°C, kg/ltr	0.885
Viscosity @ 40°C, cSt	106
Viscosity @ 100°C, cSt	14.4
Viscosity Index	139
SAE Number	15W-40
Base Number	10.5
Closed Flash Point, °C	>200
Pour Point, °C	-39

